

Commercial Dishwasher Hood Type 47 Rack

Rs. 247200(GST Extra)

The hood-type dishwasher is for the reliable washing of glasses and dishes. The model for washing heavily soiled wash ware in fast cycles. The hood-type dishwasher is perfectly suited for high utilization in restaurants and catering facilities.

The hood-type dishwasher is characterized by fast cycle times. The integrated drain heat recovery system transfers the heat from the hot drain water to the fresh-water supply, reducing the boiler power consumption and saving up to 36 % of costs.



Technical Specifications :

Capacity	: 47 Rack / Hour
Housing Material	: Stainless Steel
Type	: Fully-Automatic
Power	: 2000 W
Frequency	: 50 Hz
Weight	: 68 kg
Dimension	: 748x833x1515/1970
Electric Supply voltage	: 380-400V / 3Phase / 50Hz
Default Installed Power	: 12.9 kW
Boiler heating elements	: 12 kW
Boiler reducible to	: 6 kW
Tank heating elements	: 3 kW
Wash pump size	: 0,8 kW
Water supply temperature	: 10-60 °C
Inlet Water supply pressure	: 7 - 102 psi (0.5 - 7 bar)
Water consumption per cycle	: 3 L
Boiler Capacity	: 12 L
Tank Capacity	: 42L
Drain line size	: 40mm

Features :

High-efficiency air gap

20 Apr 2024 - Price Valid For 15 days

No 55, Sri Ram Nagar, Bharathiar University Post, vadavalli, Coimbatore - 641 046. Phone: 9489110117

ashwin@cookkart.in | <https://www.cookkart.in/>

4 second (variable) pause after washing and before rinsing

Three-phase electrical connection, convertible to single phase on-site

Automatic start on hood closure

Low noise level

Self-draining wash pump and boiler

A fully automatic self-cleaning cycle avoids the risk of bacteria proliferation

Pre-arranged to accept external dispensers

Open the hood on the backside to prevent steam blasts to the operator.

54/90/150 seconds "high productivity" cycle

Application : To Wash Dishes

Warranty : 1 Year

Product Video :

Technical Specifications

Boiler Capacity	12 L
Boiler heating elements	12 kW
Boiler reducible to	6 kW
Default Installed Power	12.9 kW
Dimension	748x833x1515/1970
Drain line size	40mm
Electric Supply voltage	380-400V / 3Phase / 50Hz
Frequency	50 Hz
Housing Material	Stainless Steel
Inlet Water supply pressure	7 - 102 psi (0.5 - 7 bar)
Power	2000 W
Tank Capacity	42L
Tank heating elements	3 kW
Wash pump size	0,8 kW
Water consumption per cycle	3 L
Water supply temperature	10-60 °C
Weight in Kgs	68 kg
Capacity	47 Rack / Hour
Type	Fully-Automatic

20 Apr 2024 - Price Valid For 15 days

No 55, Sri Ram Nagar, Bharathiar University Post, vadavalli, Coimbatore - 641 046. Phone: 9489110117

ashwin@cookkart.in | <https://www.cookkart.in/>